

Package: rspmapi (via r-universe)

September 2, 2024

Title R Wrapper Around The RStudio Package Manager API

Version 0.0.0.9000

Description Provides functions for querying the RStudio Package Manager API. If your organisation uses RStudio Packaeg Manager, this package will allow you to interact with it's API directly from R without having to construct the queries manually.

License MIT + file LICENSE

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.1.2

Imports httr2, magrittr

Repository <https://sellorm.r-universe.dev>

RemoteUrl <https://github.com/sellorm/rspmapi>

RemoteRef HEAD

RemoteSha 7601632f64c9e9fee475f0bd5f3e89908c88661c

Contents

| | |
|-------------------------------------|---|
| alerts | 2 |
| instance | 2 |
| metrics_packages | 3 |
| repos | 3 |
| repos_first_transaction | 4 |
| repos_packages | 4 |
| repos_packages_sysreqs | 5 |
| repos_sources | 5 |
| repos_sysreqs | 6 |
| return_endpoint | 6 |
| sources | 7 |
| sources_packages | 7 |
| sources_packages_releases | 8 |

| | |
|--------------------------------|-----------------|
| 2 | <i>instance</i> |
| sources_transactions | 8 |
| status | 9 |
| Index | 10 |

| | |
|--------|---------------------------------|
| alerts | <i>Fetches a list of alerts</i> |
|--------|---------------------------------|

Description

Fetches a list of alerts for events such as excessive file usage

Usage

```
alerts(instance)
```

Arguments

instance An `rspm_instance` object created with `instance()`.

| | |
|----------|---|
| instance | <i>Connect to an RStudio Package Manager instance</i> |
|----------|---|

Description

Connect to an RStudio Package Manager instance

Usage

```
instance(url, silent = FALSE)
```

Arguments

url string The URL of the Package Manager instance
silent boolean Silences the connection status message

| | |
|------------------|--|
| metrics_packages | <i>Fetches usage data from the metrics API</i> |
|------------------|--|

Description

This API takes two possible parameters resulting in a URL of the form: /__api__/metrics/packages?_sourceType=r&_da

Usage

```
metrics_packages(instance, params = list())
```

Arguments

| | |
|----------|--|
| instance | An rspm_instance object created with instance(). |
| params | A list of optional query parameters |

| | |
|-------|--------------------------------------|
| repos | <i>Fetches lists of repositories</i> |
|-------|--------------------------------------|

Description

Fetches lists of repositories

Usage

```
repos(instance, params = list())
```

Arguments

| | |
|----------|--|
| instance | An rspm_instance object created with instance() |
| params | A list of optional parameters applied to the API query |

repos_first_transaction

Fetches the date of the earliest calendar transaction for a repo

Description

Fetches the date of the earliest calendar transaction for a repo. Considers only transactions that are viable for calendar-based snapshots.

Usage

```
repos_first_transaction(instance, id)
```

Arguments

| | |
|----------|---|
| instance | An rsprm_instance object created with instance(). |
| id | An RSPM repository ID |

repos_packages

Fetches lists of packages for a specific repository with optional filters

Description

Fetches a single package for a specific repository with optional parameters

Usage

```
repos_packages(instance, id, name = NULL, params = list())
```

Arguments

| | |
|----------|--|
| instance | An rsprm_instance object created with instance() |
| id | An RSPM repository ID |
| name | A package name |
| params | A list of optional parameters applied to the API query |

repos_packages_sysreqs

Fetches lists of system requirements for a specific repository and package

Description

Fetches lists of system requirements for a specific repository and package

Usage

```
repos_packages_sysreqs(instance, id, name, params = list())
```

Arguments

| | |
|----------|--|
| instance | An rsprm_instance object created with instance() |
| id | An RSPM repository ID |
| name | A package name |
| params | A list of optional parameters applied to the API query |

repos_sources

Fetches lists of source records for a specific repository

Description

Fetches lists of source records for a specific repository

Usage

```
repos_sources(instance, id, params = list())
```

Arguments

| | |
|----------|--|
| instance | An rsprm_instance object created with instance() |
| id | An RSPM repository ID |
| params | A list of optional parameters applied to the API query |

`repos_sysreqs`*Fetches list of system requirements for a specific repository***Description**

Fetches list of system requirements for a specific repository

Usage

```
repos_sysreqs(instance, id, params = list())
```

Arguments

| | |
|-----------------------|---|
| <code>instance</code> | An <code>rspm_instance</code> object created with <code>instance()</code> |
| <code>id</code> | An RSPM repository ID |
| <code>params</code> | A list of optional parameters applied to the API query |

`return_endpoint`*The generic endpoint access function***Description**

builds appropriate query strings and performs requests against the supplied RSPM instance

Usage

```
return_endpoint(instance, endpoint, params = list())
```

Arguments

| | |
|-----------------------|--|
| <code>instance</code> | An RSPM instance object created with <code>instance()</code> |
| <code>endpoint</code> | The API endpoint to query |
| <code>params</code> | Optional list of query parameters |

| | |
|---------|---|
| sources | <i>Fetches lists of sources available in RSPM</i> |
|---------|---|

Description

Fetches lists of sources available in RSPM

Usage

```
sources(instance)
```

Arguments

| | |
|----------|---|
| instance | An rspm_instance object created with instance() |
|----------|---|

| | |
|------------------|--|
| sources_packages | <i>Fetches lists of packages for a specific source with optional filters</i> |
|------------------|--|

Description

Fetches lists of packages for a specific source with optional filters

Usage

```
sources_packages(instance, id, params = list())
```

Arguments

| | |
|----------|--|
| instance | An rspm_instance object created with instance() |
| id | An RSPM source ID |
| params | A list of optional parameters applied to the API query |

sources_packages_releases

Fetches lists of PyPI package releases for a specific package name and source with optional filters

Description

Fetches lists of PyPI package releases for a specific package name and source with optional filters

Usage

```
sources_packages_releases(instance, id, name, params = list())
```

Arguments

| | |
|----------|--|
| instance | An rspm_instance object created with instance() |
| id | An RSPM source ID |
| name | A package name |
| params | A list of optional parameters applied to the API query |

sources_transactions *Fetches lists of transactions for a given source*

Description

Fetches lists of transactions for a given source

Usage

```
sources_transactions(instance, id, params = list())
```

Arguments

| | |
|----------|--|
| instance | An rspm_instance object created with instance(). |
| id | An RSPM source ID |
| params | A list of optional parameters applied to the API query |

| | |
|--------|---|
| status | <i>Fetches the status of the RStudio Package Manager server</i> |
|--------|---|

Description

Fetches the status of the RStudio Package Manager server

Usage

```
status(instance)
```

Arguments

| | |
|----------|---|
| instance | An <code>rspm_instance</code> object created with <code>instance()</code> . |
|----------|---|

Index

alerts, 2
instance, 2
metrics_packages, 3
repos, 3
repos_first_transaction, 4
repos_packages, 4
repos_packages_sysreqs, 5
repos_sources, 5
repos_sysreqs, 6
return_endpoint, 6

sources, 7
sources_packages, 7
sources_packages_releases, 8
sources_transactions, 8
status, 9